

HOSE CONTAINMENT GRIPS

DOUBLE EYE

APPLICATIONS

Hose containment grips are designed to prevent whipping of pressurised hose in the event of the hose separating from the fitting. The Chinese finger style design grips the hose in the unlikely event of separation which helps to prevent injury to operators or damage to nearby equipment.

FEATURES

- Two eye design ensures secure anchored connections
- The breaking load displayed in the table represents a strength of guarantee and safety

MATERIAL

Wire: Galvanized / Stainless / Kevlar

Ferrules: Aluminum

Thimbles: Stainless Steel

Leg Protection: Spiral Guards (Colour Coded)

Standard range can be varied with stainless steel wire and thimbles and 316SS stainless steel or copper ferrules at your request.



TWO EYE HOSE RESTRAINT GALVANISED

#	Wire Size	Diameter	Grip Length	Overall Length	Breaking load	Shackle
	mm	min - max (mm)	mm	mm	kg	tonne
HR2E01	1.2	6 - 14	330	420	1600	0.75
HR2E02	1.2	14 - 20	365	455	1600	0.75
HR2E03	1.5	20 - 30	580	695	2500	0.75
HR2E04	2.0	30 - 40	820	985	4200	1
HR2E05	2.0	40 - 50	900	1085	4200	1
HR2E06	2.5	50 - 60	1220	1450	7500	1.5
HR2E07	2.5	60 - 70	1230	1470	7500	1.5
HR2E08	2.5	70 - 85	1300	1560	7500	1.5
HR2E09	3.0	85 - 100	1600	1900	10500	2
HR2E10	3.0	100 - 120	1715	2105	10500	2
HR2E11	4.0	120 - 140	2050	2500	16000	3.2
HR2E12	4.0	140 - 180	2800	3300	20000	3.2
HR2E13	4.0	180 - 220	3100	3650	20000	3.2
HR2E14	4.0	220 - 260	3500	4050	20000	3.2
HR2E15	4.0	260 - 300	3600	4180	20000	3.2

TWO EYE HOSE RESTRAINT 316SS

#	Wire Size	Diameter	Grip Length	Overall Length	Breaking load	Shackle
	mm	min - max (mm)	mm	mm	kg	tonne
HR2E01SS	1.2	6 - 14	330	420	1300	0.75
HR2E02SS	1.2	14 - 20	365	455	1300	0.75
HR2E03SS	1.6	20 - 30	580	695	2000	0.75
HR2E04SS	2.0	30 - 40	820	985	3500	1
HR2E05SS	2.0	40 - 50	900	1085	3500	1
HR2E06SS	2.5	50 - 60	1220	1450	6500	1.5
HR2E07SS	2.5	60 - 70	1230	1470	6500	1.5
HR2E08SS	2.5	70 - 85	1300	1560	6500	1.5
HR2E09SS	3.2	85 - 100	1600	1900	9000	2
HR2E10SS	3.2	100 - 120	1715	2105	9000	2
HR2E11SS	4.0	120 - 140	2050	2500	12000	3.2
HR2E12SS	4.0	140 - 180	2800	3300	16000	3.2

HOSE CONTAINMENT GRIPS

SAFETY SHACKLES

TWO EYE HOSE RESTRAINT KEVLAR (ARAMID FIBRE)

#	Wire Size	Diameter	Grip Length	Overall Length	Breaking load	Shackle
	mm	min - max (mm)	mm	mm	kg	tonne
HR2E02K	2.5	14 - 20	320	450	1600	0.75
HR2E03K	2.5	20 - 30	500	640	1600	0.75
HR2E04K	2.5	30 - 40	670	830	2100	1.0
HR2E05K	2.5	40 - 50	800	960	2100	1.0



SAFETY SHACKLES

5 sizes of safety bow with a safety pin. These are suitable for our hose restraints and can be purchased as an 'add on' or separately.

#	Diameter
	min - max (mm)
Safety 75	0.75
Safety 100	1.0
Safety 150	1.5
Safety 200	2.0
Safety 320	3.2



OPTIONAL HOSE RESTRAINT CONFIGURATIONS

- Four Eye Hose Restraint.
- Single Eye Cable Stocking.
- Offset Eye Cable Stocking.
- Twin Eye Cable Stocking.
- Open Ended Cable Stocking.
- Lace-up Cable Stocking.