

AS / NZS 1869 LPG GAS HOSE



Product specifications

#							
	inch	mm	mm	bar	psi	kg/m	mm
7132-19352	3/16	4.8	13.0	24.1	350	0.05	50.8
7132-25354	1/4	6.4	15.5	24.1	350	0.07	63.5
7132-38354	3/8	9.5	19.1	24.1	350	0.10	88.9
7132-50354	1/2	12.7	23.8	24.1	350	0.15	114.3
7132-75354	3/4	19.1	31.8	24.1	350	0.23	165.1
7132-100354	1	25.4	38.1	24.1	350	0.29	190.5

APPLICATIONS

Series 7132 is a flexible, lightweight liquefied petroleum gas (LPG) / propane delivery and transfer hose. The hose meets all Underwriters Laboratories (UL21) and Canadian Gas Association (CGA Type I) requirements. The construction incorporates multiple textile plies of reinforcement for flexibility and kink resistance. The perforated cover is resistant to mild chemicals, oil and ozone. Series 7132 is available in long lengths on reels, long cut lengths and factory-tested assemblies from stock in popular configurations.

FEATURES

- Extremely flexible
- Kink resistant
- AS1869 approved

CONSTRUCTION

Core tube: Black nitrile.
Pressure reinforcement: Multiple textile plies.
Cover: Black chloroprene; perforated smooth finish.

TEMPERATURE RANGE

-40°C to +82°C (The hose construction is capable of this rating, but LP Gas should NEVER be conveyed over 60°C/140°F).



Please Note: We reserve the right to make technical changes without notice.