







ABSWAH-40

AIR & MULTIPURPOSE



Product specifications

#									
	inch	mm	mm	bar	psi	bar	psi	kg/m	mm
AH600-0050	1/2	13.0	24.0	40	600	160	2400	0.51	130.0
AH600-0075	3/4	19.0	31.0	40	600	160	2400	0.74	133.0
AH600-0100	1	25.0	38.0	40	600	160	2400	0.91	175.0
AH600-0125	1 1/4	32.0	45.0	40	600	160	2400	1.51	224.0
AH600-0150	1 1/2	38.0	56.0	40	600	160	2400	1.93	266.0
AH600-0200	2	51.0	69.0	40	600	160	2400	2.40	357.0
AH600-0250	2 1/2	63.5	81.0	40	600	160	2400	2.90	441.0
AH600-0300	3	76.0	95.0	40	600	160	2400	4.68	532.0
AH600-0400	4	102.0	120.0	40	600	160	2400	7.34	714.0

APPLICATIONS

Designed for the most severe working conditions in mining, quarries, industrial and construction service, this mandrel built hose has a high margin safety and gives a long and trouble-free service under the most arduous working conditions.

FEATURES

- High pressure
- Weather and ozone resistant

CONSTRUCTION

Core tube: Synthetic NBR rubber, resistant to oil-mist mixed air and inert fluids.
Pressure reinforcement: High tensile steel wire.
Cover: Abrasion, ozone and weather resistant pin pricked synthetic rubber.

TEMPERATURE RANGE

-40°C to 100°C.



Please Note: We reserve the right to make technical changes without notice.