





RED VARIFLEX®

AIR & MULTIPURPOSE



RED VARIFLEX® - AIR & MULTIPURPOSE

Product specifications

#							Length
	inch	mm	mm	bar	psi	kg/m	m
20025484	1/4	6	13.5	20	300	0.15	152.4
20025485	5/16	8	16.0	20	300	0.21	152.4
20025487	3/8	10	17.5	20	300	0.22	152.4
20025490	1/2	12	21.3	20	300	0.31	152.4
20025518	5/8	16	25.4	20	300	0.40	152.4
20025493	3/4	19	28.7	20	300	0.57	152.4
20025532	1	25	38.1	20	300	0.92	137.2
20026197	1 1/4	32	45.6	17.2	250	1.11	122.0
20022906	1 1/2	38	53.2	17.2	250	1.44	91.4

APPLICATIONS

A good-quality, economical general purpose hose for industrial air service, compressor lines, pneumatic tools, low-pressure spray and many other applications where the need for oil resistance is moderate. Non-conductive, minimum electrical resistance greater than one (10) megohm per inch of length of hose at 1000 V DC.

FEATURES

- Excellent oil resistance.
- Non-conductive.
- Colour coded for different applications.

CONSTRUCTION

Core tube: Red Chemivic™ synthetic rubber. RMA Class A (high oil resistance).
Pressure reinforcement: Nitrile synthetic rubber. RMA Class A (high oil resistance).
Cover: Spiral synthetic yarn (3/16" - 1 1/2"), braided synthetic yarn (2").

TEMPERATURE RANGE

-29°C to 88°C.



Please Note: We reserve the right to make technical changes without notice.

