






ARVAC™ SW VACUUM



ARVAC™ SW - VACUUM

Product specifications

#							Vacuum HG			Length
	inch	mm	mm	bar	psi	mm	mm	inch	kg/m	m
20448195	1 1/4	31.8	40.7	3.1	45	76	737	29	0.52	100
20448194	1 1/2	38.1	47.4	2.8	40	76	737	29	0.58	100
20448193	2	50.8	62.5	2.8	40	63	737	29	0.99	100
20448192	2 1/2	63.5	77.0	2.4	35	101	737	29	1.33	100
20448191	3	76.2	91.5	2.1	30	152	737	29	1.73	100
20448190	4	101.6	120.5	2.1	30	177	737	29	2.91	100
20447689	5	127.0	147.5	2.1	30	203	737	29	3.82	100
20452698	6	152.4	175.0	1.7	25	203	737	29	4.91	20
20452697	6	152.4	175.0	1.7	25	203	737	29	4.91	50
20447688	6	152.4	175.0	1.7	25	203	737	29	4.91	100
20447687	8	203.2	232.0	1.4	20	456	737	29	8.38	20
20450354	8	203.2	232.0	1.4	20	456	737	29	8.38	50
20447686	10	254.0	283.5	1.4	20	912	737	29	11.63	20
20460651	10	254.0	283.5	1.4	20	912	737	29	11.63	40

APPLICATIONS

Heavy-duty abrasion-resistant suction hose used for a variety of abrasive material-handling applications, including the transfer of sand, gravel, cement, fly ash, glass, metals, plastic pellets, fertilizers, rock salts and slurries. Static wire for static dissipation.

FEATURES

- Lighter and more flexible than ARTRAC®.
- Higher Abrasion Resistant Core Tube.

CONSTRUCTION

Core tube: High temperature urethane.
Pressure reinforcement: Rigid high-demand PVC helix.
Cover: Static-dissipating thermoplastic alloyed blend of nitrile, polyurethane and PVC.

TEMPERATURE RANGE

-40°C to 70°C.



Please Note: We reserve the right to make technical changes without notice.

