








PLICORD® SUPER BLACK FLEXWING® PETROLEUM TRANSFER

#								Vacuum HG		
	inch	mm		bar	psi	mm	inch	mm	inch	
20155914	1 1/4	31.8	47.1	207	300	100.0	4	737.0	29	1.48
20017550	1 1/2	38.1	52.8	207	300	100.0	4	737.0	29	1.71
20017552	2	50.8	65.8	207	300	125.0	5	737.0	29	2.14
20017558	2 1/2	63.5	79.0	207	300	150.0	6	737.0	29	2.74
20017560	3	76.2	92.7	207	300	175.0	7	737.0	29	3.56
20017564	4	101.6	122.7	207	300	254.0	10	737.0	29	5.60
20017568	5	127.0	149.0	207	300	500.0	20	737.0	29	7.60
20338990	6	152.4	183.3	207	300	600.0	24	737.0	29	12.60

APPLICATIONS

A premium high-pressure petroleum transfer hose for handling ethanol blends, gasoline, oils and other petroleum products at higher working pressures.

FEATURES

- Premium quality
- Weather and ozone resistant
- Early warning system for external wear

CONSTRUCTION

Core tube: Special fuel-resistant black nitrile synthetic rubber RMA Class A (High oil resistance)

Pressure reinforcement: Spiral-plied synthetic fabric with wire helix

Cover: Black Chemivic™ smooth cover with wrapped finish. Also available with ARC treatment for improved abrasion resistance. Both hoses standard with built in blue wear ply to illustrate wear condition and potential trigger point for product replacement.

TEMPERATURE RANGE

-37°C to 93°C.



Please Note: We reserve the right to make technical changes without notice.