







V404 PETROLEUM TRANSFER

Product specifications

#							Length
	inch	mm	mm	bar	psi	kg/m	m
20572398	3/4	19.0	29.0	10.3	150	0.59	30.0
20572399	1	25.0	36.0	10.3	150	0.83	30.0
20574515	1	25.0	36.0	10.3	150	0.83	60.0
20572400	1 1/4	32.0	43.0	10.3	150	1.07	30.0
20574516	1 1/4	32.0	43.0	10.3	150	1.07	60.0
20572401	1 1/2	38.0	49.0	10.3	150	1.21	30.0
20574517	1 1/2	38.0	49.0	10.3	150	1.21	60.0
20572402	2	50.0	63.0	10.3	150	1.76	30.0
20574518	2	50.0	63.0	10.3	150	1.76	60.0
20572403	2 1/2	63.0	77.0	10.3	150	1.59	30.0
20574520	2 1/2	63.0	77.0	10.3	150	1.59	60.0
20572404	3	75.0	89.0	10.3	150	2.83	30.0
20574521	3	75.0	89.0	10.3	150	2.83	60.0
20572397	4	100.0	118.0	10.3	150	4.67	30.0

APPLICATIONS

General purpose hose used to transfer gasoline, oil and other petroleum based products. Hose is designed for pressure, gravity flow or suction service.

FEATURES

- Premium quality
- Weather and ozone resistant

CONSTRUCTION

Core tube: NBR (Oil resistant).
Pressure reinforcement: Synthetic fabric plies (2) with wire helix.
Cover: Black NBR (Oil resistant); wrapped finish.
Branding: Veyance V404 oil suction and delivery WP150psi

TEMPERATURE RANGE

-20°C to 70°C.



Please Note: We reserve the right to make technical changes without notice.