






# KANAFLEX - KANAVAC HR (180 HR)

## SUCTION & DISCHARGE



### Product specifications

#									Vacuum	Pitch	Length
	inch	mm	inch	mm	bar	psi	inch	kg / m	in / hg	inch	ft / mtr
KF180HR-100	4	102	4.69	119	2.07	30	5.5	0.80	29.8	0.65	100 / 30.48
KF180HR-150	6	152	6.9	175	2.07	30	9.8	1.57	28.0	0.87	100 / 30.48
KF180HR-200	8	203	9.13	232	2.07	30	15.0	2.72	27.0	0.87	100 / 30.48

### APPLICATIONS

Heavy-duty abrasion resistant suction applications where high temperature and abrasion are factors such as vacuum trucks or the handling of fresh ash, crushed rock, sand, pea gravel, or cement powder.

### FEATURES

- Lightweight and flexible.
- Integral wire helix can be grounded.
- External helix provides easy drag.
- Rated up to 104°C / 220°F.

### CONSTRUCTION

**Core tube:** EPDM rubber.  
**Pressure reinforcement:** Polyethylene helix, metal helical wire, smooth bore, corrugated O.D.  
**Cover:** Black.

### TEMPERATURE RANGE

-40°C to 104°C.  
 -40°F to 220°F.

**Kanaflex**

**Please Note:** We reserve the right to make technical changes without notice.