







MSD300

MULTI SUCTION & DISCHARGE



Product specifications

| # |  | |  | |  | |  | |  |  | Vacuum | |
|-------------|---|-------|---|-----|---|-----|---|-------|---|---|--------|----|
| | mm | inch | mm | bar | psi | bar | psi | kg/m | | | mm | mm |
| MSD300-0200 | 51 | 2 | 65 | 20 | 300 | 60 | 900 | 1.98 | 250 | 737 | 29 | |
| MSD300-0250 | 64 | 2 1/2 | 79 | 20 | 300 | 60 | 900 | 2.62 | 330 | 737 | 29 | |
| MSD300-0300 | 76 | 3 | 93 | 20 | 300 | 60 | 900 | 3.40 | 420 | 737 | 29 | |
| MSD300-0400 | 102 | 4 | 120 | 20 | 300 | 60 | 900 | 4.91 | 600 | 737 | 29 | |
| MSD300-0500 | 127 | 5 | 149 | 20 | 300 | 60 | 900 | 7.15 | 750 | 737 | 29 | |
| MSD300-0600 | 152 | 6 | 174 | 20 | 300 | 60 | 900 | 9.25 | 950 | 737 | 29 | |
| MSD300-0800 | 203 | 8 | 230 | 20 | 300 | 60 | 900 | 9.92 | 1500 | 737 | 29 | |
| MSD300-1000 | 254 | 10 | 288 | 20 | 300 | 60 | 900 | 21.44 | 1750 | 737 | 29 | |
| MSD300-1200 | 306 | 12 | 343 | 20 | 300 | 60 | 900 | 29.06 | 2400 | 737 | 29 | |

APPLICATIONS

Heavy duty suction and delivery hose, excellent for use as a tank truck or tank wagon hose; it withstands the full vacuum; its anti-static cover conforms fully to PTB specifications; used for a wide range of petroleum products up to 50% aromatic content.

FEATURES

- Weather and Ozone Resistant.
- Anti Static Cover.

CONSTRUCTION

Core tube: Black, smooth, nitrile rubber compounded.
Pressure reinforcement: High strength synthetic cord plus helix wires and anti-static copper wire.
Cover: Black, smooth (wrapped finish) high grade chloroprene rubber, compounded for an excellent resistance to weather, ozone, abrasion and oil resistant; antistatic.
Coil: 61 mt (200ft) continuous length; other lengths available on request.

TEMPERATURE RANGE

-40°C to 100°C.

Please Note: We reserve the right to make technical changes without notice.