






# PUREONE CHEMICAL SUCTION



## Product specifications

#										Vaccum	
	size	inch	mm	inch	mm	bar	psi	mm	kg/m	in	mm
20950668	3/4	0.75	19.1	1.20	30.5	13.8	200	102	0.65	29	737
20950669	1	1.00	25.4	1.46	36.9	13.8	200	102	0.85	29	737
20950720	1 1/4	1.25	31.8	1.70	43.3	13.8	200	102	1.01	29	737
20950721	1 1/2	1.50	38.1	1.95	49.6	13.8	200	127	1.19	29	737
20950722	2	2.00	50.8	2.52	63.9	13.8	200	152	1.71	29	737
20950724	3	3.00	76.2	3.61	91.7	13.8	200	229	3.07	29	737
20950725	4	4.00	101.6	4.62	117.4	13.8	200	254	4.04	29	737

## APPLICATIONS

Suitable for suction and discharge service, it will handle the majority of common industrial chemicals used today (please check chemical reference chart for recommendations). PureOne is suitable for potable water applications and other food applications such as transferring high-proof alcohol. Suitable for DEF.

## FEATURES

- High Chemical Resistance.
- Extreme Flexibility.
- Lightweight.
- Suitable for Potable Water - Food Industry Standards.

## CONSTRUCTION

**Core tube:** UHMWPE conforms to FDA, USDA, 3-A standards and NSF-61 listed materials.  
**Pressure reinforcement:** Synthetic fabric with double wire helix.  
**Cover:** Blue abrasion and ozone resistant EPDM rubber.

## TEMPERATURE RANGE

-40°C to 100°C.