

P35-32

2" - 5,000 PSI OIL FIELD HOSE



Hydraulic and cementing applications

#										
	mm	inch	mm	bar	psi	bar	psi	mm	kg/m	
P35-32	50.8	2	71.0	350	5,000	1400	20,000	630.0	7.48	

APPLICATIONS

General high pressure large flow hydraulic applications (construction, injection moulding, mining, oil drilling), as well as cementing and mud circulation. Suitable for use with Petroleum based hydraulic fluids and lubricating oils.

FEATURES

- Meets SAE 100R13, ISO 3861-1 Type R13 and EN 856 Type R13
- High abrasion MSHA rated cover
- Long lengths available, up to 45m
- Integral hammer unions available

CONSTRUCTION

Core tube: Synthetic rubber.
Pressure reinforcement: Four or six spiral steel wire.
Cover: Synthetic rubber, MSHA accepted.
Inner Tube: Synthetic rubber.


TEMPERATURE RANGE

-40°C to +125°C.

FITTINGS


1502 Hammerlug union female

#		A	B	
		mm	mm	bar
1HNS6-32-32	4 1/8 - 3 ACME	190.0	94.4	1035




1502 Hammerlug union male

#		A	B	
		mm	mm	bar
1HES6-32-32-FLAT	4 1/8 - 3 ACME	207.0	113.0	1035



Male NPTF pipe - rigid

#			A	B	
	inch		mm	mm	inch
101S6-32-32	2	2 x 11 - 1/2	150.0	62.0	2 1/2






Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.




P35-32

2" - 5,000 PSI OIL FIELD HOSE

Female JIC 37° - swivel

#	 inch	 2 1/2 x 12	A mm	B inch	 inch
106S6-32-32	2	2 1/2 x 12	166.0	2 7/8	2 1/2



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.