

# P5675

## 2" - 8,000 PSI OIL FIELD HOSE



### Drilling and cementing applications

#									
	mm	inch	bar	psi	bar	psi	mm	kg/m	
P5675	51	2	75.0	552	8,000	1400	20,000	630.0	7.89

### APPLICATIONS

Oil and weather resistant, abrasion resistant MSHA cover. General high pressure large flow hydraulic applications (construction, injection moulding, mining, oil drilling), as well as cementing and mud circulation. Suitable for use with Petroleum based hydraulic fluids and lubricating oils.

### FEATURES

- Ultra Abrasion resistant wrapped cover
- Twice the abrasion resistance of standard rubber
- Integral Hammer Union Fittings available
- Long lengths available, up to 45m

### CONSTRUCTION

**Core tube:** Synthetic rubber.  
**Pressure reinforcement:** 6 spiral plies of high tensile steel wire.  
**Cover:** Oil and weather resistant, black, synthetic rubber and heavy UHMWPE abrasion resistant MSHA cover.  
**Inner Tube:** Synthetic rubber.


### TEMPERATURE RANGE

-40°C to +70°C.

### FITTINGS


#### 1502 Hammerlug union female

#		A	B	
		mm	mm	bar
1HNS6-32-32	4 1/8 - 3 ACME	190.0	94.4	1035




#### 1502 Hammerlug union male

#		A	B	
		mm	mm	bar
1HES6-32-32-FLAT	4 1/8 - 3 ACME	270.0	113.0	1035




#### Male NPTF pipe - rigid

#			A	B	
	inch		mm	mm	inch
101S6-32-32	2	2 x 11 - 1/2	150.0	62.0	2 1/2



#### Female JIC 37° - swivel

#			A	B	
	inch		mm	mm	inch
106S6-32-32	2	2 1/2 x 12	166.0	78.0	2 1/2



**Please Note:** Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.