



2448M-32V88

2" - 5,000 PSI GOLDEN EAGLE

Chemical applications

#									Test pressure			Collapse pressure	Max length
	mm	inch	mm	inch	bar	psi	bar	psi					
2448M-32V88	50.5	2	82.0	3.23	345	5,000	1380	20,000	518	500.0	8.50	49	600

APPLICATIONS

Suitable for use in cementing, acidizing and water / chemical injection applications. Increased chemical resistance and temperature rating when compared to standard Black Eagle.

FEATURES

- Short term use to +100°C
- Suitable for use with aggressive chemicals such as hydrochloric acid
- ColorGard, visual early warning system
- Long continuous lengths available

CONSTRUCTION

Core tube: Fluoropolymer based inner core.
Pressure reinforcement: 4 layers of high tensile steel wire.
Cover: Extra thick dual layer TPU sheath.
Colour: ColorGard™ – red inner sheath and golden outer sheath.


TEMPERATURE RANGE

-40°C up to +70°C / -40°F up to 158°F.

FITTINGS


NPT Male fitting

#		A	B	ØR	
		mm	mm	mm	bar
101BL-32-32	2 NPT	275.0	129.0	83.0	690




1502 Hammerlug union female

#		A	B	
		mm	mm	bar
1HNBL-32-32	4 1/8 - 3 ACME	263.0	117.0	1035




1502 Hammerlug union male

#		A	B	
		mm	mm	bar
1HEBL-32-32-FLAT	4 1/8 - 3 ACME	278.3	132.3	1035



1502 Hammerlug union male, segmented

#		A	B	
		mm	mm	bar
1HEBL-32-32-SEG	4 1/8 - 3 ACME	278.3	132.3	1035



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.