



# 2580M-32V88

## 2" - 10,000 PSI GOLDEN EAGLE

### Chemical applications

#									Test pressure			Collapse pressure	Max length
	mm	inch	mm	inch	bar	psi	bar	psi					
2580M-32V88	50.5	2	84.5	3.33	690	10,000	1725	25,000	1075	800.0	9.40	57	600

### APPLICATIONS

Suitable for use in cementing, acidizing and water / chemical injection applications. Increased chemical resistance and temperature rating when compared to standard Black Eagle.

### FEATURES

- Short term use to +100°C
- Suitable for use with aggressive chemicals such as hydrochloric acid
- Colorgard, visual early warning system
- Long continuous lengths available
- Fluoropolymer based

### CONSTRUCTION

**Core tube:** Fluoropolymer based inner core.  
**Pressure reinforcement:** 4 layers of high tensile steel wire.  
**Cover:** Extra thick dual layer TPU sheath.  
**Colour:** ColorGard™ – red inner sheath and golden outer sheath.


### TEMPERATURE RANGE

-40°C up to +70°C / -40°F up to 158°F.

### FITTINGS


#### NPT Male fitting

#		A	B	ØR	
		mm	mm	mm	bar
101BL-32-32	2 NPT	275.0	129.0	83.0	690




#### 1502 Hammerlug union female

#		A	B	
		mm	mm	bar
1HNBL-32-32	4 1/8 - 3 ACME	263.0	117.0	1035




#### 1502 Hammerlug union male

#		A	B	
		mm	mm	bar
1HEBL-32-32-FLAT	4 1/8 - 3 ACME	278.3	132.3	1035



#### 1502 Hammerlug union male, segmented

#		A	B	
		mm	mm	bar
1HEBL-32-32-SEG	4 1/8 - 3 ACME	278.3	132.3	1035



**Please Note:** Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.