


2" DRILLING HOSE

2" - 5,000 PSI OIL FIELD HOSE



Hose applications

mm	inch	mm	bar	psi	bar	psi	mm	kg/m			
68.4	2.69	72.0	350	5,070	1500	21,750	630.0	6.8			

APPLICATIONS

General high pressure large flow hydraulic applications (construction, injection moulding, mining, oil drilling), as well as mud circulation. Suitable for use with Petroleum based hydraulic fluids and lubricating oils. As a flexible connection for conveying mud at pressures up to 5000 psi max. Rotary drilling, water well operations, high pressure fluid transfer.

FEATURES

- Approved at 1,000,000 flexing impulse cycles
- Superior abrasion resistance
- High ozone and weather resistance
- Flame resistance to a wide range of specification
- Biological and mineral oils compatibility
- Integral matched FIG1502 Hammer Unions
- NPTLP API Thread for use with threaded Hammer Unions, Hubs and Flanges
- Perforated cover for Air / Gas applications
- 4:1 Safety factor

CONSTRUCTION

Core tube: Oil resistant synthetic rubber.
Pressure reinforcement: Four high tensile steel spirals (DN 6-25).
 Six high tensile steel spirals (DN 31-51).
Cover: Synthetic rubber with high ozone, weather and heat resistance.


TEMPERATURE RANGE

-40°C to +121°C.

FITTINGS


1502 Hammerlug union female

	A	B	
	mm	mm	bar
4 1/8 - 3 ACME	286.0	149.0	1035



1502 Hammerlug union male

	A	B	
	mm	mm	bar
4 1/8 - 3 ACME	241.0	105.0	1035



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.