

BLACK GOLD® ROTARY VIBRATOR 5000 POWERSPIRAL™



Hose applications

								Length
mm	inch	mm	inch	bar	psi	mm	lbs / per ft	ft
76	3	98	3.86	345	5,000	889	6.80	200

APPLICATIONS

Flexible connection between standpipe and top drive / swivel or between pump and standpipe for pumping mud at extra high pressure in oil drilling and exploration work. Meets the severe demands of today's drilling methods including directional drilling, pressure pulses and elevated temperatures.

FEATURES

- Crimped GSM. Available with a full range of fitting options such as Hammer Unions, Flanges, Hubs, etc.
- API Spec 7K (6th Edition). ISO 14693. ABS and DNV-GL type approvals.
- Accessories such as safety clamps, hose lift eyes and stainless steel armour are available upon request.

CONSTRUCTION

Core tube: Type C2 (Modified Nitrile). Black.
Pressure reinforcement: High tensile steel wire.
Outer cover: Type A (Chlorprene). Black with gold stripe.
Design Factor: 2.5:1

STANDARDS

API Spec 7K (6th Edition). ISO II.J693. ABS and DNV-GL type approvals.

TEMPERATURE RANGE

-4°F to +250°F (-20°C to +121°C) continuous service.

Please Note: We reserve the right to make technical changes without notice.