






SLIM HOLE ROTARY DRILL SERIES 7234



Hose applications

#							
	inch	mm		bar	psi		
7234-3000	3	76.2	3.780	206.8	3000	1104.9	lbs / per ft 2.09

APPLICATIONS

Series 7234 is a heavy duty, high pressure, versatile hose designed to handle cement solutions, mild chemicals, oil and water in oilfield applications such as rotary service on portable drilling units, reverse circulation systems, seismic equipment and workover rigs. The hose construction incorporates multiple plies of high tensile wire reinforcement that provide high pressure capability, crush resistance, durability, kink resistance and a path to conduct a static electrical charge to ground. The synthetic rubber cover is resistant to abrasion, oil and weathering.

FEATURES

- Cement solutions, mild chemicals, oil, water.
- Portable drilling units, workover rigs.
- General industrial, oil field.
- 40mtr long lengths available.

CONSTRUCTION

Core tube: Black synthetic rubber.
Pressure reinforcement: Multiple wire plies.
Outer cover: Black synthetic rubber; wrapped finish.
Safety factor: Design factor 3" ID 2.5:1

TEMPERATURE RANGE

-40°C to +93°C.

AVAILABLE FITTINGS

- 3" NPT Male.
- 3" 1-Piece FIG 1502 Hammer Unions.
- Customised Butt weld options available on request.



Please Note: We reserve the right to make technical changes without notice.