



2240N-32V10

2" - 3,000 PSI BLACK EAGLE LIGHT

Hose applications

#									Test pressure bar			Collapse pressure bar	Max length mtr
	mm	inch	mm	inch	bar	psi	bar	psi					
2240N-32V10	51	2	68.5	2.70	207	3,000	827	12,000	311	500.0	4.4	38	1,000

APPLICATIONS

Cementing operations, acidizing, mud circulation, general fluid and gas injection.

FEATURES

- PA11 core tube with inner ColorGuard™
- Significantly higher abrasion resistance than common elastomer materials
- Longer service life and less contamination in cement slurry
- Easy visualization of core tube erosion - more efficient product inspection and reduced unscheduled downtime
- Lighter weight and smaller O.D. than common 4-layer constructions - faster and easier deployment
- DNV Type approval to API 7K

CONSTRUCTION

Core tube: PA11 with inner ColorGuard™.
Pressure reinforcement: 2 layers of high tensile steel wire.
Cover: Extra thick TPU sheath.
Colour: Black.


TEMPERATURE RANGE

-40°C up to +100°C / -40°F up to 212°F.

FITTINGS


Hammerlug union female - Onshore: Special steel materials.

#		A	B	
		mm	mm	bar
1HNS6-32-32	4 1/8 - 3 ACME	190.0	94.4	1035




Hammerlug union male - Onshore: Special steel materials.

#		A	B	
		mm	mm	bar
1HES6-32-32-FLAT	4 1/8 - 3 ACME	207.0	113.0	1035




Hammerlug union female - Offshore: Special steel and stainless steel materials.

#		A	B	
		mm	mm	bar
1HNS6-32-32-SC	4 1/8 - 3 ACME	190.0	94.4	1035



Hammerlug union male - Offshore: Special steel and stainless steel materials.

#		A	B	
		mm	mm	bar
1HES6-32-32-FLAT-SC	4 1/8 - 3 ACME	207.0	113.0	1035



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.