

2248N-32V10

2" - 5,000 PSI BLACK EAGLE LIGHT



Hose applications

| # | | | | | | | | | Test pressure | | | Collapse pressure | Max length |
|-------------|----|------|------|------|-----|-------|-----|--------|---------------|-------|------|-------------------|------------|
| | mm | inch | mm | inch | bar | psi | bar | psi | bar | mm | kg/m | bar | mtr |
| 2248N-32V10 | 51 | 2 | 68.5 | 2.70 | 345 | 5,000 | 862 | 12,500 | 518 | 500.0 | 4.4 | 38 | 1,000 |

APPLICATIONS

Cementing operations, acidizing, mud circulation, general fluid and gas injection.

FEATURES

- PA11 core tube with inner ColorGard™
- Significantly higher abrasion resistance than common elastomer materials
- Longer service life and less contamination in cement slurry
- Easy visualization of core tube erosion - more efficient product inspection and reduced unscheduled downtime
- Lighter weight and smaller O.D. than common 4-layer constructions - faster and easier deployment
- DNV Type approval to API 7K

CONSTRUCTION

Core tube: PA11 with inner ColorGard™.
Pressure reinforcement: 6 spiral layers of high tensile steel wire.
Cover: Extra thick TPU sheath.
Colour: Black.


TEMPERATURE RANGE

-40°C up to +100°C / -40°F up to 212°F.

FITTINGS


Hammerlug union female - Onshore: Special steel materials.

| # | | A | B | |
|-------------|----------------|-------|------|------|
| | | mm | mm | bar |
| 1HNS6-32-32 | 4 1/8 - 3 ACME | 190.0 | 94.4 | 1035 |




Hammerlug union male - Onshore: Special steel materials.

| # | | A | B | |
|------------------|----------------|-------|-------|------|
| | | mm | mm | bar |
| 1HES6-32-32-FLAT | 4 1/8 - 3 ACME | 207.0 | 113.0 | 1035 |




Hammerlug union female - Offshore: Special steel and stainless steel materials.

| # | | A | B | |
|----------------|----------------|-------|------|------|
| | | mm | mm | bar |
| 1HNS6-32-32-SC | 4 1/8 - 3 ACME | 190.0 | 94.4 | 1035 |



Hammerlug union male - Offshore: Special steel and stainless steel materials.

| # | | A | B | |
|---------------------|----------------|-------|-------|------|
| | | mm | mm | bar |
| 1HES6-32-32-FLAT-SC | 4 1/8 - 3 ACME | 207.0 | 113.0 | 1035 |



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.