

2SN-DRAIN / JW-BLUE

RUBBER DRAIN / SEWER CLEANING HOSE



Drain / sewer cleaning applications

#											
	mm	inch	mm	bar	psi	bar	psi	mm	kg/m		
2SN-4-DRAIN	6.4	1/4	15.0	400	5800	1600	23200	100.0	0.33		
JW-4-BLUE	6.4	1/4	13.4	400	5800	1600	23200	75.0	0.29		
2SN-6-DRAIN	9.5	3/8	18.8	330	4800	1320	19200	125.0	0.50		
JW-6-BLUE	9.5	3/8	17.1	400	5800	1600	23200	90.0	0.42		
2SN-8-DRAIN	12.7	1/2	22.2	276	4000	1104	16000	178.0	0.65		
JW-8-BLUE	12.7	1/2	20.7	400	5800	1600	23200	130.0	0.58		
2SN-12-DRAIN	19.0	3/4	29.3	215	3100	860	12400	240.0	0.86		
2SN-16-DRAIN	25.4	1	37.2	165	2400	660	9600	300.0	1.28		

APPLICATIONS

Medium – high pressure water jetting applications to include drain, sewer and stack pipe cleaning / unblocking, the JW version is also excellent for the higher temperature requirements with a range of up to +150°C.

FEATURES

- High abrasion resistance
- High ozone and weather resistance
- Flame resistance to a wide range as specifications
- Applicable specifications: EN 853 2SN – SAE R100 R2AT

CONSTRUCTION

Core tube: Synthetic rubber.
Pressure reinforcement: Two high tensile steel wire braids.
Cover: 2SN: Synthetic rubber, MSHA flame retardant approved.
 JW: Synthetic rubber smooth finish, pin pricked.
Colour: 2SN: Black. JW: Blue.

TEMPERATURE RANGE

Water
 2SN: -40°C up to +85°C.
 JW: -40°C up to +150°C.

Hydraulic
 2SN: -40°C up to 100°C (occasional peaks up to +125°C).



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.