







ISOBARIC RUBBER HOSE

210 BAR XTRAFLEX



Hydraulic application

#											
	DN	dash	inch	mm	bar	psi	bar	psi	mm	lb/ft	
H10093031	32	-20	1 1/4	44.5	210	3,040	840	12,180	210.0	2.07	
H10093038	38	-24	1 1/2	52.1	210	3,040	840	12,180	260.0	2.9	
H10093051	51	-32	2	66.8	210	3,040	840	12,180	330.0	4.3	

APPLICATIONS

Medium and high pressure hydraulic lines for general hydraulics. Return lines of hydraulic systems. Oils (up to 100°C / 212°F), glycols and polyglycols, mineral oils in aqueous emulsion, water.

FEATURES

- Good flexibility in the whole temperature range
- High impulse resistance according to ISO 18752 requirements
- Weight saving vs traditional R12 hose construction
- Isobaric pressure rating for easy selection and product management

CONSTRUCTION

Core tube: Oil resistant synthetic rubber.
Pressure reinforcement: 4 high tensile steel spirals.
Cover: Synthetic rubber with high abrasion, ozone, weather and heat resistance.

TEMPERATURE RANGE

-40°C / +100°C

FITTINGS

A wide range of fittings are available.
 Please contact our sales team for further information.

Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request.
 We reserve the right to make technical changes without notice.