



JACKING HOSE

TWO WIRE RUBBER JACKING HOSE

Hydraulic - Jacking hose

#									
	mm	inch		bar	psi	bar	psi		
JK-4	6.3	1/4	15.0	724	10,500	1448	21,000	100.0	0.39
JK-6	10.0	3/8	22.0	700	10,000	1400	20,000	125.0	0.55

APPLICATIONS

Hydraulic Jacking systems where a reduced safety factor is acceptable. Suitable for use close to welding applications.

FEATURES

- High static pressure. Tested / approved for specific jacking applications
- High flexibility
- Applicable specifications: IJ100 hydraulic jack spec
- This product has a 2:1 Safety Factor

CONSTRUCTION

Core tube: Nitrile or neoprene synthetic rubber.
Pressure reinforcement: Two braids steel wire.
Cover: Synthetic rubber, MSHA accepted.


TEMPERATURE RANGE

-40°C to +100°C.

FITTINGS

Male NPTF pipe - rigid

#			A	B		Stainless Steel (C)
10143-2-4	1/4	1/8 x 27	46.0	27.0	9/16	-
10143-4-4	1/4	1/4 x 18	51.0	22.0	9/16	✓
10143-6-4	1/4	3/8 x 18	47.0	28.0	11/16	-
10143-4-6	3/8	1/4 x 18	58.0	32.0	3/4	-
10143-6-6	3/8	3/8 x 18	60.0	34.0	3/4	✓



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.