



Transportation applications

#									
	mm	inch		bar	psi	bar	psi		
206-4	5.0	3/16	13.2	207	3,000	830	12,000	75.0	0.22
206-5	6.3	1/4	14.8	207	3,000	860	12,000	85.0	0.27
206-6	8.0	5/16	17.1	155	2,250	620	9,000	90.0	0.34
206-8	10.0	13/32	19.5	138	2,000	550	8,000	90.0	0.40
206-10	12.5	1/2	23.4	122	1,750	480	7,000	100.0	0.55
206-12	16.0	5/8	27.4	103	1,500	410	6,000	100.0	0.60
206-16	22.0	7/8	31.4	55	800	220	3,200	100.0	0.68
206-20	29.0	1 1/8	38.1	43	625	170	2,500	140.0	0.76
206-24	35.0	1 3/8	44.5	35	500	140	2,000	190.0	1.01
206-32	46.0	1 13/16	56.4	24	350	100	1,400	335.0	1.32

APPLICATIONS

Petroleum based hydraulic fluids and lubricating oils, diesel fuels and anti-freeze solutions.

FEATURES

- Available with field attachable fittings
- Can also be used on vacuum type applications
- DOT air brake certification

CONSTRUCTION

Core tube: PKR - elastomer tube.
Pressure reinforcement: One fibre braid and one steel braid.
Cover: Fibre braid, blue.


TEMPERATURE RANGE

-48°C to +150°C.

FITTINGS

Male NPTF pipe - rigid




#			A	B		Additional Material
10126-2-4	3/16	1/8 x 27	42.0	20.0	0.78	-
10126-4-4	3/16	1/4 x 18	48.0	26.0	1.01	-
10126-4-5	1/4	1/4 x 18	48.0	26.0	1.01	-
10126-4-6	5/16	1/4 x 18	48.0	26.0	1.02	✓
10126-6-6	5/16	3/8 x 18	48.0	26.0	1.03	✓
10126-6-8	13/32	3/8 x 18	48.0	26.0	1.03	✓
10126-8-8	13/32	1/2 x 14	54.0	33.0	1.28	✓
10126-8-10	1/2	1/2 x 14	57.0	33.0	1.30	✓
10126-12-12	5/8	3/4 x 14	59.0	35.0	1.37	✓
10126-16-16	7/8	1 x 11 - 1/2	66.0	40.0	1.57	-
10126-20-20	1 1/8	1 1/4 x 11 - 1/2	72.0	45.0	1.77	-
10126-24-24	1 3/8	1 1/2 x 11 - 1/2	76.0	49.0	1.93	-
10126-32-32	1 13/16	2 x 11 - 1/2	87.0	55.0	2.18	-




Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request.
 We reserve the right to make technical changes without notice.







Female JIC 37° - swivel

#			A	B		Additional Material
	inch		mm	mm	inch	Brass
10626-6-6	5/16	9/16 x 18	45.0	23.0	1 1/16	✓
10626-6-8	13/32	9/16 x 18	52.0	30.0	1 1/16	✓
10626-12-12	5/8	1 1/16 x 12	58.0	34.0	1 1/4	✓
10626-16-16	7/8	1 5/16 x 12	64.0	38.0	1 1/2	✓
10626-20-20	1 1/8	1 5/8 x 12	65.0	38.0	2	✓
10626-24-24	1 1/2	1 7/8 x 12	70.0	43.0	2 1/4	-
10626-32-32	1 13/16	2 1/2 x 12	84.0	52.0	2 7/8	-



Female JIC 37° / SAE 45° - dual flare - swivel

#			A	B		Additional Material
	inch		mm	mm	inch	Brass
16826-4-4	3/16	7/16 x 20	42.0	20.0	9/16	✓
16826-4-5	1/4	7/16 x 20	48.0	26.0	9/16	-
16826-4-6	5/16	7/16 x 20	39.0	17.0	9/16	-
16826-5-5	1/4	1/2 x 20	45.0	23.0	5/8	-
16826-8-6	5/16	3/4 x 16	56.0	34.0	7/8	-
16826-8-8	13/32	3/4 x 16	49.0	27.0	7/8	-
16826-8-10	1/2	3/4 x 16	60.0	36.0	7/8	✓
16826-10-10	1/2	7/8 x 14	55.0	31.0	1	✓
16826-10-12	5/8	7/8 x 14	61.0	37.0	1	-



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.