

GOLDENBLAST™ PLUS WATERBLAST



Waterblast applications

#										
	DN	size	inch	mm	bar	psi	bar	psi	mm	kg/m
H10066010	10	-06	3/8	20.0	1250	18,120	3125	45,320	230.0	0.8
H10066A12	12	-08	1/2	24.1	1100	15,950	2750	39,880	230.0	1.11
H10066019	19	-12	3/4	32.0	1000	14,500	2500	36,250	250.0	1.73
H10066025	25	-16	1	38.1	700	10,150	1750	25,370	250.0	2.04

APPLICATIONS

High pressure water blasting used for heavy construction, ship building/main tenance and general industrial cleaning applications. Hydro- demolition (including the removal of concrete and marine paint). High pressure grease injection.

FEATURES

- High abrasion resistant cover, suited to harsh applications
- High kink resistance and large through bore ID to improve flow rate and reduce pressure drop
- Available in lengths up to 40m

CONSTRUCTION

Core tube: Water resistant synthetic rubber.
Pressure reinforcement: Four spiral layers of maximum tensile steel wire.
Cover: Synthetic rubber.

TEMPERATURE RANGE


-10°C / +70°C.

FITTINGS

*Stainless steel 316 available - Please prefix the part numbers above with the letter "I".


NPTF Male 60° cone seat: SAE J516/JS14 – M57810.

#					A	B	C	
	DN	size	inch					
M57810-06-06	10	-06	3/8	3/8 - 18	38.0	8.5	15.5	22.0
M57810-08-08	12	-08	1/2	1/2 - 14	44.6	10.00	21.0	27.0
M57810-12-12	20	-12	3/4	3/4 - 14	49.4	15.0	21.0	32.0
M57810-16-16	25	-16	1	1 - 11.5	55.0	19.5	24.2	41.0



Metric O-ring female 24° cone heavy duty: DIN 20066/ISO – M66613.

#					A	B	C	
	DN	size	inch					
M66613-06-22	10	-06	3/8	M22 x 1.5	32.0	4.8	3.5	27.0
M66613-06-24	10	-06	3/8	M24 x 1.5	34.2	6.3	4.0	32.0
M66613-08-24	12	-08	1/2	M24 x 1.5	35.4	7.5	4.0	32.0
M66613-12-36	20	-12	3/4	M36 x 2	44.7	12.0	3.4	46.0
M66613-16-42	25	-16	1	M42 x 2	43.5	19.5	5.3	50.0







Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.



GOLDENBLAST™ PLUS WATERBLAST

BSP 60° Female cone, double thrust-wire nut: BS5200/ISO – 12151-6.

#						A	B	C	
	DN	size	inch			mm	mm	mm	mm
M65514-06-06	10	-06	3/8 BSP	3/8 BSP Female		34.5	4.8	6.0	24.0
M65514-08-08	12	-08	1/2 BSP	1/2 BSP Female		37.0	7.5	6.5	30.0
M65514-12-12	19	-12	3/4 BSP	3/4 BSP Female		43.0	12.0	8.7	36.0



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.