



SAFESHEILD WATERBLAST

Waterblast applications

#			mm	bar	psi			mm	
	mm	inch				bar	psi		
EC910-08	12.7	1/2	24.6	1100	16,000	2750	40,000	228.6	1.12
EC910-12	19.0	3/4	32.8	1000	14,500	2500	36,250	279.4	1.75

APPLICATIONS

Water treatment facilities. Marine surfaces, runway cleaning, paint removal, bridge renovation. Waterblast service with water, water-soap emulsion. Exceeds ISO 7751 requirements.

FEATURES

- Four spiral wire construction
- Eaton's highly abrasion resistant DURA-TUFF hose cover
- 2.5:1 hose safety factor
- Meets global specifications EN1829-2 (impulse) and AS / NZ4233.2
- Superior hose flexibility provides ease of use in the field

CONSTRUCTION

Core tube: Water resistant synthetic rubber.
Pressure reinforcement: Six high tensile steel spirals
Cover: Synthetic rubber with very high temperature, ozone and abrasion resistance.


TEMPERATURE RANGE

-10°C to +70°C.

FITTINGS


Male NPTF

#				A	E
	DN	size			
FW1889-0808S	12	-08	1/2 - 14	77.1	9.0
1W12MP12	19	-12	3/4-14	92.1	15.1



Metric O-ring female 24° cone heavy duty

#				A	E
	DN	size			
GH10235-8W	12	-08	M24 x 1.5	74.0	9.0
1W20DS12	19	-12	M36 x 2.0	103.2	15.1



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.