


SEMPERJET 2 SN WATERBLAST



General applications

#									
	mm	inch		bar	psi	bar	psi		
RJ2SN-04	6	1/4	13.4	400	5,800	1600	23,206	100	0.19
RJ2SN-05	8	5/16	16.0	400	5,800	1400	20,305	115	0.22
RJ2SN-06	10	3/8	18.4	400	5,800	1320	19,144	125	0.28
RJ2SN-08	12	1/2	21.4	400	5,800	1100	15,945	180	0.36

APPLICATIONS

High pressure hose for pressure washer applications, exceeds EN 1829-2. Dimensions and tolerances acc. to DIN EN 853 2 SN. For cold and hot water jet wash cleaners up to 155°C (310°F) peak temperature.

FEATURES

- High pressure for pressure washer applications.
- High temperature resistance.

CONSTRUCTION

Core tube: Synthetic rubber, resistant against cold and hot water with usual cleaning agents.

Pressure reinforcement: Two braids of high tensile steel wire.

Cover: Abrasion and ozone resistant synthetic rubber.
NB. Black, blue, and grey cover available.


TEMPERATURE RANGE

-10°C to 155°C.

FITTINGS

BSP Female Swivel

#				A	B
	DN	Inch			
200667	-4	1/4	1/4 BSP Female Swivel	1/4	1/4
200951	-5	5/16	3/8 BSP Female Swivel	3/8	5/16
200952	-6	3/8	3/8 BSP Female Swivel	3/8	3/8
200645	-8	1/2	1/2 BSP Female Swivel	1/2	1/2



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.