

P250 TEST BENCH

MODULAR TEST BENCH

P250



Technical data

	P250
Test pressure	150 - 1500 bar
Control	C.2 IPC
Drive	Intensifier
Flow rate (effectively)	7.5 l/min
Air supply	7 bar 60 NI/min
Tank dimensions (mm)	2194 x 890 x 470
Test bench dimensions	2700 x 1450 x 1550 mm
Reservoir capacity	120L
Loading (kg)	250
Weight (kg)	570
Noise level	75 dBA
Electrical connection	3 VAC
Options	
High pressure	150 - 3000 bar
Low pressure	20 - 1500 bar
Stainless steel tank	✓
Extended version on request L x W x H (mm)	2220 x 1000 x 1400
Weight (kg)	420

FEATURES & BENEFITS

- Fully enclosed test chamber.
- Suitable for static pressure testing of various hydraulic components such as valves, hydraulic cylinders, housings, quick-release couplings, etc.
- Safety switch - when the hood is opened, all pressure is automatically released within 1/10 second.
- Environmentally friendly test medium (water-oil emulsion).
- Easy and safe to operate.
- Quick changeover between automated and manual setup mode.
- Test bench can be retrofitted with extension element.
- Up to 120 tests per hour for a max. length of 2 500 mm (DN 12-800 mm).



Concept, design and complete!