



2448D TOUGH COVER WATER JETTING

Hydraulic and water jetting applications

#	Ø				Ø		⌚		🌿		📐		Kg kg/m
	DN	size	mm	inch	mm	bar	psi	bar	psi	mm			
2448D-025V32-TC	4	-025	4.0	5/32	9.9	325	47,120	6500	94,240	100.0		0.21	

APPLICATIONS

Ultra-high pressure service for tube cleaning applications such as heat exchanging in the chemical and oil refining industries, Marine cleaning and water jet cutting.

FEATURES

- Meets or exceeds the requirements of DIN EN 1829-2. This standard prescribes that the hose assemblies have to resist at least 20,000 impulse cycles amongst other challenges
- Tough Cover is up to 40% more resistant to abrasion over Standard Version
- Compact design
- Resistant against hydrolysis, ozone and UV radiation

CONSTRUCTION

Core tube: Polyoxymethylene.
Pressure reinforcement: Four spiral layers of maximum tensile steel wire.
Cover: Polyamide.
Colour: Blue.


TEMPERATURE RANGE

-10°C up to +70°C.

FITTINGS

UNF Male nozzle nipple: Stainless steel.


#	Ø				🌿	A	B	⌚	
	DN	size	mm	inch				bar	psi
6YHLYX-4-2AC-PL*	4	-025	4.0	5/32	1/4 - 28 UNF	58.0	26.0	2800	40,600
6YHLYX-4-2AC-PL-LH*	4	-025	4.0	5/32	1/4 - 28 UNF LH	58.0	26.0	2800	40,600



*ProLance fitting.

UNF Female for water jetting nozzle: Stainless steel.

#	Ø				🌿	A	B	⌚	
	DN	size	mm	inch				bar	psi
6HYLX-4-2AC-PL*	4	-025	4.0	5/32	1/4 - 28 UNF	51.0	19.0	2800	40,600
6HYLX-4-2AC-PL-LH*	4	-025	4.0	5/32	1/4 - 28 UNF LH	51.0	19.0	2800	40,600
6HYLX-6-2AC-PL-LH*	4	-025	4.0	5/32	3/8 - 24 UNF LH	49.0	21.0	2800	40,600



*ProLance fitting.







Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.

2448D TOUGH COVER WATER JETTING








High pressure tube nipple UNF - LH Thread: Stainless steel.

#						A	B		
	DN	size	mm	inch				mm	mm
6Y4LX-4-2AC	4	-025	4.0	5/32	1/4 - 28 UNF LH	75.0	44.0	4000	58,000
6Y4LX-6-2AC	4	-025	4.0	5/32	3/8 - 24 UNF LH	86.0	55.0	4000	58,000



Type "M" female swivel: Stainless steel.

#						A	B			
	DN	size	mm	inch					mm	mm
6AYLX-6-2AC	4	-025	4.0	5/32	9/16 - 18 UNF	64.0	33.0	17.0	3010	43,645



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.