

HOSE CRIMPING MACHINES AT A GLANCE

	Crimp Force	Control	SAE R12 / 4SP	Industrial	Elbows	Crimp range	Crimp path	Opening	Page
S 1 M	750 / 75	Micrometer	1"	1 1/4"	1/2"	52mm	5mm	+10mm	478
S 1 P	750 / 75	Micrometer	1"	1 1/4"	1/2"	52mm	5mm	+10mm	478
S 2 E	900 / 90	Micrometer	1"	1 1/4"	1"	63mm	8mm	+22mm	479
S 2 M	900 / 90	Micrometer	1"	1 1/4"	1"	63mm	8mm	+22mm	480
S 2 P	900 / 90	Micrometer	1"	1 1/4"	1"	63mm	8mm	+22mm	480
S 2 A	900 / 90	Micrometer	1"	1 1/4"	1"	63mm	8mm	+22mm	480
S 3 E	1200 / 120	Control A	1 1/4"	2"	1 1/2"	70mm	8mm	+35mm	485
S 4	1800 / 180	B + Touch	1 1/2"	2"	1 1/2"	70mm	8mm	+35mm	485
S 6	2000 / 200	B + Touch	2"	3"	2"	100mm	8mm	+45mm	486
S 7	2400 / 240	Open / Close	2"	2"	1 1/2"	82mm	8mm	+24mm	482
S 8	2200 / 220	Control A	2"	4"	2"	139mm	8mm	+45mm	487
S 10	2800 / 280	Control A	2"	4"	2"	139mm	8mm	+45mm	487
UA4	1350 / 135	Micrometer	1 1/4"	1 1/2"	2"	57mm	8mm	+15mm	484
HM 200	1300 / 130	Control A	1 1/4"	2"	1 1/2"	70mm	8mm	+30mm	483
HM 220	1400 / 140	C + Touch	1 1/4"	2"	1 1/2"	70mm	8mm	+35mm	468
HM 225	1600 / 160	C + Touch	1 1/4"	2"	1 1/2"	70mm	8mm	+40mm	468
HM 245	750 / 75	C + Touch	3"	1"	1 1/4"	70mm	8mm	+35mm	469
HM 3 H	700 / 70	C + Touch	1"	2"	1 1/2"	70mm	8mm	+35mm	488
HM 325	2800 / 280	C + Touch	2"	4" (6")	3"	165mm	20mm	+70mm	467
HM 375	3150 / 315	C + Touch	3"	4" (6")	3"	165mm	20mm	+70mm	467
HM 380	3400 / 340	C + Touch	3"	4" (6")	3"	165mm	20mm	+70mm	467
HM 450	4000 / 400	C + Touch	3"	10"	3"	310mm	80mm	+150mm	470
HM 480	4500 / 450	C + Touch	3"	10"	3"	310mm	80mm	+150mm	470
HM 485	4500 / 450	C + Touch	3"	10"	3"	250mm	20mm	+310mm	470
HM 495	6000 / 600	C + Touch	3"	10"	3"	310mm	80mm	+150mm	470
HM 660	8000 / 800	C + Touch	3"	10"	3"	325mm	50mm	+120mm	471
HM 665	4500 / 450	C + Touch	3"	10"	3"	380mm	50mm	+120mm	471
HM 1200	12000 / 1200	C + Touch	3"	10"	3"	325mm	50mm	+120mm	471
HMC12 - 2000	20,000 / 2000	Control C.2	3"	12"	3"	380mm	50mm	-	472



The best return on Investment since 1972.

HOSE CRIMPING MACHINES AT A GLANCE

	Opening without dies	Type of dies	Speed - Close	Speed - Crimp	Speed - Open	Drive	Noise level	Ecoline	Page
S 1 M	52mm	261	-	-	-	Manual	-	-	478
S 1 P	52mm	261	1,0	1,0	-	Pressure	-	-	478
S 2 E	77mm	263	-	-	-	Manual	-	✓	479
S 2 M	77mm	263	-	-	-	Manual	-	-	480
S 2 P	77mm	263	0,9	0,9	-	Pressure	-	-	480
S 2 A	77mm	263	5,8	0,6	-	Electric	-	-	480
S 3 E	105mm	239	4	4	6,5	3 kW	69 dBA	✓	485
S 4	105mm	239	2,7	2,7	4,7	4 kW	69 dBA	✓	485
S 6	147mm	239 / 266L	9,7	2,2	16	5,5 kW	69 dBA	✓	486
S 7	110mm	239 / 265	-	1,42	-	0,55 kW	70 dBA	-	482
S 8	190mm	239 / 237L	6,1	1,7	10,3	4 kW	69 dBA	✓	487
S 10	190mm	239 / 237L	6,1	1,7	10,3	5,5 kW	69 dBA	✓	487
UA4	73mm	280	-	-	-	0,75 kW	-	-	484
HM 200	100mm	239	3,5	3,5	5,9	3 kW	69 dBA	✓	483
HM 220	105mm	239	9,5	6	9,5	5,5 kW	53 dBA	-	468
HM 225	110mm	239	19	1,5	19	5,5 kW	53 dBA	-	468
HM 245	105mm	239	27	5	30	5,5 kW	53 dBA	-	469
HM 3 H	105mm	239	8,6	8,6	10,5	5,5 kW	53 dBA	-	488
HM 325	215mm	239 / 237L	23	1,4	33	4 kW	62 dBA	-	467
HM 375	215mm	239 / 237L	23	1,4	33	4 kW	62 dBA	-	467
HM 380	215mm	239 / 237L	23	1,3	33	4 kW	62 dBA	-	467
HM 450	380mm	239 / 237L / 245	20	1,5	23	5,5 kW	62 dBA	-	470
HM 480	380mm	239 / 237L / 245	20	1,5	23	5,5 kW	62 dBA	-	470
HM 485	360mm	239 / 237L / 245	20	1,5	23	5,5 kW	62 dBA	-	470
HM 495	380mm	239 / 237L / 245	20	1,5	23	5,5 kW	62 dBA	-	470
HM 660	395mm	239 / 237L / 246L	15	2	15	18,5 kW	69 dBA	-	471
HM 665	450mm	239 / 237L / 247L	15	2	15	18,5 kW	69 dBA	-	471
HM 1200	395mm	239 / 237L / 246L	11	1,5	11	18,5 kW	69 dBA	-	471
HMC12 - 2000	435mm	247L / 245L / 237L	-	-	-	-	-	-	472



The best return on Investment since 1972.