

WORKSHOP CRIMPERS MEDIUM DUTY PRODUCTION



HM 200



HM 200 Ecoline



Technical data

	HM 200	HM 200 Ecoline
Crimp force (kN/Ton)	1300 / 130	1300 / 130
Crimp range	70mm	70mm
SAE R12 / 4SH* 1 Piece	1 1/2"	1 1/2"
SAE R15 / 4SH* 2 Piece	1"	1"
SAE R12 / 4SH* 2 Piece	1 1/4"	1 1/4"
Industrial**	2"	2"
90° Elbows	1 1/2"	1 1/2"
Speed (seconds) - Close	3,5	3,5
Speed (seconds) - Crimp	3,5	3,5
Speed (seconds) - Open	5,9	5,9
No grease: 20% less friction	✓	✓
Control	Control A	Ecoline
Opening	+ 30mm	+ 30mm
Opening without dies	100mm	100mm
Type of dies	239	239
Drive	3 kW	3 kW
Oil	40 L	40 L (DC 4 L)
Weight	140 kg	88 kg
L x W x H (mm)	800 x 530 x 630	420 x 535 x 520
Power unit L x W x H (DC)	-	420 x 535 x 520
Noise Level	69 dBA	69 dBA

Options	HM 200	HM 200 Ecoline
12 / 24 Volt	-	✓
1 Phase	✓	2,2 kW

D Types of die	PB239-XX-D Length (mm)
6.8	50
9	50
10	50
12	50
14	60
16	60
17	60
19	60
20	60
22	60
24	60
26	75
28	75
32	75
36	75
40	75
44	75
47	75
50	75
54	75
57	75
62	75

Package dies.

* Fittings may vary. ** Without flange.

Package

QDS 239 B QDC 239.5



Optional Extras (See page 463)



HM 200 Ecoline 12V package comes with 12 x dies, die rack and quick die changing tool. See page 540.



The best return on Investment since 1972.