

PORTABLE HEAVY DUTY CRIMPERS

FLEXIBLE CRIMP DIAMETER



S2 A / S2 DC



Technical data

	S2 A	S2 DC
Crimp force (kN/Ton)	900 / 90	900 / 90
Crimp range	63mm	63mm
SAE R12 / 4SH* 1 Piece	1 1/4"	1 1/4"
SAE R15 / 4SH* 2 Piece	1"	1"
Industrial**	1 1/4"	1 1/4"
90° Elbows	1"	1"
Speed (seconds) - Close	5,8	2,4
Speed (seconds) - Crimp	0,6	0,2
No grease: 20% less friction	✓	✓
Opening	+ 22mm	+ 22mm
Opening without dies	77mm	77mm
Type of dies	263	263
Drive	1 Phase electric	12 Volt / 24 Volt
Oil	1,5 L	1,5 L
Weight	41 kg	41 kg
L x W x H (mm)	500 x 420 x 440	170 x 220 x 330

D Types of die	PB263-XX-D Length (mm)
6.8	40
9	75
12	75
14	75
17	75
20	75
24	75
28	75
32	75
36	75
40	75
44	75
47	75

Package dies.

* Fittings may vary. ** Without flange.

FEATURES & BENEFITS

- Adjustable micrometer
- Fast for the operator
- 12V DC for mobile operation

Package

QPS 261 B



The best return on Investment since 1972.