

WORKSHOP CRIMPERS MEDIUM DUTY PRODUCTION



S3 Ecoline
S4 Ecoline



S4 B



Technical data

	S3 Ecoline	S4 Ecoline	S4
Crimp force (kN/Ton)	1200 / 120	1800 / 180	1800 / 180
Crimp range	70mm	70mm	70mm
SAE R12 / 4SH* 1 Piece	1 1/4"	2"	2"
SAE R15 / 4SH* 2 Piece	1"	1 1/4"	1 1/4"
SAE R12 / 4SH* 2 Piece	1 1/4"	2"	2"
Industrial	2"	2"	2"
90° Elbows	1 1/2"	1 1/2"	1 1/2"
Speed (seconds) - Close	4	2,7	2,7
Speed (seconds) - Crimp	4	2,7	2,7
Speed (seconds) - Open	6,5	4,7	4,7
No grease: 20% less friction	✓	✓	✓
Control	Control A	Control A	Control B + Touch
Opening	+ 35mm	+ 35mm	+ 35mm
Opening without dies	105mm	105mm	105mm
Type of dies	239	239	239
Drive	3 kW	3 kW	3 kW
Oil	35 L	35 L	35 L
Weight	150 kg	160 kg	203 kg
L x W x H (mm)	592 x 545 x 672	592 x 545 x 672	720 x 600 x 672
Noise level	69 dBA	69 dBA	69 dBA
Options	S3 Ecoline	S4 Ecoline	S4
12 / 24 Volt	✓	✓	-
1 Phase	✓	✓	-

* Fittings may vary.

Package

QDS 239 B QDC 239.5



Optional Extras (See page 463)



S3 Ecoline

D Types of die	PB239-XX-D Length (mm)
6.8	50
9	50
10	50
12	50
14	50
16	65
17	65
19	65
20	65
22	65
24	65
26	65
28	80
32	80
36	80
40	80
44	80
47	100
50	100
54	100
57	100
62	100

S4 Ecoline / S4

D Types of die	PB239-XX-D Length (mm)
6.8	50
9	50
10	50
12	50
14	50
16	65
17	65
19	65
20	65
22	65
24	65
26	65
28	80
32	80
36	80
40	80
44	80
47	100
50	100
54	100
57	100
62	100

Package dies (both machines up to includes 40mm).



The best return on Investment since 1972.