



S6



S6 Light



S6 Light DC



Technical data

	S6 Ecoline	S6	S6 Light	S6 Light DC
Crimp force (kN/Ton)	2000 / 200	2000 / 200	2000 / 240	2800 / 240
Crimp range	100mm	100mm	100mm	100mm
SAE R 15 / 4SH* 1 Piece	2"	2"	2"	2"
4SH* 2 Piece	2"	2"	2"	2"
SAE R 15 / 4SH* 2 Piece	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Industrial	3"	3"	3"	3"
No grease: 20% less friction	✓	✓	✓	✓
Control	Control A	Control A	Control A	Control A
90° Elbows	2"	2"	2"	2"
Opening	+ 45mm	+ 45mm	+ 41mm	+ 41mm
Opening without dies	147mm	147mm	143mm	143mm
Type of dies	239-xx / 266	239-xx / 266	239-xx / 266	239-xx / 266
Noise Level	69 dBA	69 dBA	69 dBA	69 dBA
Drive	4 kW	4 kW	3 kW	1,8 kW
Oil	50 L	70 L	35 L	4 L
Weight	248 kg	374 kg	190 kg	145 kg
L x W x H (mm)	700 x 600 x 735	690 x 600 x 1350	600 x 550 x 750	505 x 430 x 490
Speed (seconds) - Close	4,9	9,7	1,5	1,1
Speed (seconds) - Crimp	2,3	2,2	1,5	0,3
Speed (seconds) - Open	8,2	16	8,7	6,5


D Types of die	PB239-XX-D Length mm	PB237-XX-D Length mm
6.8	50	-
9	50	-
10	50	-
12	65	-
14	65	-
16	65	-
17	65	-
19	65	-
20	65	-
22	65	-
24	65	-
26	65	-
28	65	-
30	80	-
31	80	-
32	80	-
36	80	-
38	80	-
39	80	-
40	80	-
44	80	-
47	80	-
50	100	-
54	100	-
57	100	-
62	100	110
67	-	110
71	-	110
74	-	110
78	-	110
84	-	110
86	-	110
92	-	110

* Fittings may vary.

Options	S6 Ecoline	S6	S6 Light	S6 Light DC
12 / 24 Volt	-	-	-	✓
1 Phase	✓	-	✓	-
3 Phase	✓	✓	✓	-

Package

QDS 239 B QDC 239.5



NO RESTRICTIVE HOSE CRIMPING



Package dies include adaptor die set.



The best return on Investment since 1972.