

S6 STRONG

SERVICE CRIMPERS

S6 Strong



S6 Strong Ecoline



Technical data

	S6 Strong	S6 Strong Ecoline
Crimp force (kN / Ton)	2800 / 280	2800 / 280
No grease: 20% less friction	✓	✓
Control	Control A	Control A
SAE R 15 / 4SH* 1 piece fitting	2"	2"
4SH* 2 piece fitting	2"	2"
SAE R 15* 2 piece fitting	2"	2"
Industrial	3"	3"
90° Elbows	2"	2"
Max. Crimp range	100mm	100mm
Opening	+ 45mm	+ 45mm
Opening without dies	147mm	147mm
Master dies length	110mm	110mm
Type of dies	239-xx/266**	239-xx/266**
Speed (mm/sec) - Close	3.0	6
Speed (mm/sec) - Crimp	1.4	1.4
Speed (mm/sec) - Open	5.3	13.6
Noise level	69 dBA	69 dBA
Drive	4 kW 3 VAC	4 kW 3 VAC
Oil	50 L	70 L
L x W x H (mm)	700 x 600 x 735	745 x 600 x 1360
Weight	320 kg	450 kg
Options		
12 VDC / 24 VDC	-	-
1 Phase	✓	-
3 Phase	-	-
Control C.2	✓	✓

Ø Types of die mm	239-xx-Ø-yy mm	266 mm
6,8	50	
9	50	
10	50	
12	65	
14	65	
16	65	
17	65	
19	65	
20	65	
22	65	
24	65	
26	65	
28	80	
30	80	
31	80	
32	80	
36	80	
38	80	
39	80	
40	80	
44	80	
47	100	
50	100	
54	100	
57	100	
62	100	110
67		110
71		110
78		110
84		110
86		110
92		110

* According to the fitting. ** Intermediate dies not required, only S6.

Package

QDS 239 B QDC 239.5

