

# WORKSHOP CRIMPERS

## MEDIUM DUTY PRODUCTION



S6



S6 Ecoline



S6 Ecoline DC



### Technical data

	S6	S6 Ecoline / DC	
Crimp force (kN/Ton)	2000 / 200	2000 / 200	
Crimp range	100mm	100mm	
SAE R15 / 4SH* 1 Piece	2"	2"	
4SH* 2 Piece	2"	2"	
SAE R15 / 4SH* 2 Piece	1 1/2"	1 1/2"	
Industrial	3"	3"	
90° Elbows	2"	2"	
Speed	-	Phase 3	Phase 1
Speed (seconds) - Close	9,7	4,9	3,6
Speed (seconds) - Crimp	2,2	2,3	1,3
Speed (seconds) - Open	16	8,2	6,1
No grease: 20% less friction	✓	✓	
Control	Control B + Touch	Control A	
Opening	+ 45mm	+ 45mm	
Opening without dies	147mm	147mm	
Type of dies	239 L / 266 L	239 L / 266 L	
Drive	4 kW	4 kW	
Noise Level	69 dBA	69 dBA	
Oil	55 L	50 L	
Weight	374 kg	248 kg	
L x W x H (mm)	690x600x1350	700x600x735	

Options	S6	S6 Ecoline / DC
12 / 24 Volt	-	✓
1 Phase	-	✓
3 Phase	-	✓

Ø Types of die	239-xx-Ø-yy	266-xx-Ø-yy
6,8	50	40
9	50	-
12	50	-
14	50	-
16	65	-
17	65	-
19	65	-
20	65	-
22	65	-
24	65	-
26	65	-
28	80	-
32	80	-
36	80	-
40	80	-
44	80	-
47	100	-
50	100	-
54	100	-
57	100	110
62	100	110
67	-	110
71	-	110
74	-	110
78	-	110
84	-	110
86	-	110
92	-	110

\* Fittings may vary.

Package dies include adaptor die set.

### Package

QDS 239 B    QDC 239.5



### Optional Extras (See page 463)



The best return on Investment since 1972.