

# PORTABLE CRIMPERS - SEMI AUTOMATIC FAST CRIMP



S7 / S7 DC



## Technical data

	S7 / S7 DC
Crimp force (kN/Ton)	2400 / 240
Crimp range	82mm
SAE R15 / 4SH* 1 Piece	2"
4SH* 2 Piece	2"
SAE R15* 2 Piece	1 1/2"
Industrial	2"
90° Elbows	1 1/2"
Speed (seconds) - Close	Manual + 0.42
Speed (seconds) - Crimp	Manual + 0.42
Speed (seconds) - Open	Manual + 0.42
No grease: 20% less friction	✓
Control	Open / Close
Opening	+ 24mm
Opening without dies	110mm
Type of dies	239 / 265 L
Noise Level	70 dBA
Drive	0,75 kW
Oil	2,3 L
Weight	77 kg
L x W x H (mm)	430 x 367 x 682

Options	S7 / S7 DC
12 / 24 Volt	✓
1 Phase	✓
3 Phase	✓

D Types of die	PB239-XX-D Length (mm)	PB265-XX-D Length (mm)
6.8	50	-
9	50	-
12	50	-
14	50	-
16	65	-
17	65	-
19	65	-
20	65	-
22	65	-
24	65	-
26	65	-
28	80	-
32	80	-
36	80	-
40	80	-
44	80	-
47	100	-
50	100	-
54	100	90
57	100	90
62	100	90
67	-	90
71	-	100
74	-	100

\* Fittings may vary.

Package dies. Supplied complete with adaptor die 265.239L

## Package

QPS 261 B



## FEATURES & BENEFITS

- Combined manual and electric crimp
- Fastest possible crimping time
- Vertical crimping
- Best possible access without obstruction.



The best return on Investment since 1972.