

WORKSHOP PRODUCTION CUTTERS

HAND OPERATED & PNEUMATIC



EM 6 DC



EM 6 M



EM 6 P



Technical data

	EM 6 DC	EM 6 M	EM 6 P	EM 6 Ecoline
Production SAE R13 and SAE R15	-	1 1/4"	1 1/4"	-
Workshop SAE R13 and SAE R15	2"	2"	2"	2"
SAE R12	2"	2"	2 1/2"	2 1/2"
Industrial	2"	3"	3"	2"
Max outside diameter	Ø 75mm	Ø 85mm	Ø 90mm	Ø 80mm
Feed	Manual	Manual	Pneumatic	Manual
Noise level	93 dBA	90 dBA	90 dBA	90 dBA
Brake motor	-	✓	✓	-
Suction connection	Ø 40mm	Ø 60mm	Ø 60mm	Ø 80mm
Drive	3,2 kW : 24 VAC	4,6 kW 3 VAC	4,6 kW 3 VAC	2,4 kW 1 VAC
Cutting blade	TM C 250 x 2 x 40	TM C 350 x 3 x 30	TM C 350 x 3 x 30	TM C 275 x 3 x 25,4
L x W x H (mm)	740 x 365 x 610	745 x 690 x 430	820 x 785 x 755	700 x 510 x 700
Weight	29 kg	75 kg	110 kg	45 kg
Accessories				
Bench	✓	✓	✓	✓
Suction Device	✓	✓	✓	✓
UVC 36 Adapter	777.153	777.055	777.055	777.056
UVC 100 Adapter	330.083.3	330.081.3	330.081.3	330.082.3
Hose guide (UHG 14)	-	✓	✓	✓

Optional Extras (See page 463)



TMC, TMG and TM
High-quality cutting blades:
TM C, TM G and TM.



TMC
Lasts 7 times longer, cuts twice as fast,
generates less smoke, less debris in the
hose and less heat.
Reduces the risk of separation of the
rubber from the wire.

EM 6 Ecoline



The best return on Investment since 1972.