

HOSE TEST RIGS

WORKSHOP PRODUCTION



P 160



P 160 Ecoline



Technical data

	P 160	P 160 Ecoline
Test pressure	150 - 1300 bar	150 - 1300 bar
Drive	Intensifier	Intensifier
Flow	1,1 l / min	1,1 l / min
Capacity	7 bar, 20 l / min	7 bar, 20 l / min
Tank dimension	1590 x 795 x 370 mm	1200 x 600 x 250 mm
Test bench dimension	2210 x 950 x 1325 mm	1400 x 600 x 1200 mm
Reservoir capacity	100 l	33 l
Alternative drive filling pump 405.904 / 405.914	0,38 kW 400 V 50 Hz 3 Ph	0,5 kW 220-240 V 50/60 Hz 1 Ph
Paint	RAL 5012 Blue RAL 7021 Grey	RAL 5012 Blue
Weight - when empty	210 kg	120 kg
Noise level	72 dBA	72 dBA
Accessories	P 160	P 160 Ecoline
Suction filter / 100 µm	✓	✓
Air preparation unit	✓	✓
Steck-O-Adaptor (s-series only)	DN 4/6/8/10/12/ G 1/2" 405.901	DN 4/6/8/10/12/ G 1/2" 405.901
Anti-corrosive additive	EM 10 l	EM 10 l

Options	P 160	P 160 Ecoline
High pressure pump*	150 - 3000 bar	-
Low pressure pump*	20 - 150 bar	-
Test tank extension	2000 - 2400 mm	-



Retro fit data logging box and software.
Refer to page 568.

* Only one of the two options possible.

Standard
Speck-O-System



Optional Extras
(See page 494)



The best return on Investment since 1972.



Test bed extension