






C5C-XH HEAT HOSE



Hydraulic applications

#								
	inch	mm		bar	psi	bar	psi	
5C5CXH	1/4	6	14.7	207	3,000	827	12,000	86
6C5CXH	5/16	8	17.0	155	2,250	620	9,000	101
8C5CXH	13/32	10	19.6	138	2,000	551	8,000	116
10C5CXH	1/2	12	23.4	120	1,750	482	7,000	139
12C5CXH	5/8	16	27.4	103	1,500	413	6,000	165
16C5CXH	7/8	22	31.2	55	800	221	3,200	187
20C5CXH	1 1/8	28	38.1	43	625	172	2,500	229

APPLICATIONS

Extremely high temperature petroleum based or phosphate ester fluids, turbo charger oil supply and hot lube oil lines. Meets the requirements of SAE J1405 performance specifications for high temperature transmission and lubrication oil systems.

FEATURES

- Acceptable for use with oil and air for maximum application flexibility.
- Has passed the tube fuel resistance requirements of SAE 30R2.

CONSTRUCTION

Core tube: Black, oil and heat-resistant synthetic polymer (CPE)
Pressure reinforcement: Braided high-tensile wire and textiles
Cover: Blue, oil and mildew-resistant polyester/textile braid

TEMPERATURE RANGE

-40°C to +150°C.

Please Note: We reserve the right to make technical changes without notice.