





Product specifications

#							Length
	inch	mm	mm	bar	psi	kg/m	m
20026239	1/4	6.4	15.5	34.5	500	0.25	152.4
20026255	5/16	7.9	17.5	34.5	500	0.30	152.4
20026256	3/8	9.5	18.6	34.5	500	0.33	152.4
20026273	1/2	12.7	22.6	34.5	500	0.42	15.2
20026289	5/8	15.9	26.9	34.5	500	0.52	152.4
20026290	3/4	19.1	30.2	34.5	500	0.61	152.4
20026304	1	25.4	37.8	34.5	500	0.86	137.2
20026306	1 1/4	31.8	45.6	34.5	500	1.18	30.5
20026309	1 1/2	38.1	51.8	34.5	500	1.27	91.0
20023183	2	50.8	66.6	34.5	500	1.82	30.5

APPLICATIONS

A premium-quality, multipurpose industrial hose with a wide range of applications in factories, construction, agriculture, quarries, mines, railroads, the oil and gas industry, and shipbuilding. All sizes are rated at 500 psi (3.4 MPa) maximum working pressure. Non-conductive, minimum electrical resistance greater than one megaohm per inch of hose length at 1000 Volts DC.

FEATURES

- Premium quality
- Non-conductive
- Safety yellow cover

CONSTRUCTION

Core tube: Nitrile synthetic rubber, RMA Class A (high oil resistance).
Pressure reinforcement: Spiral flexten yarn, 2" is braided synthetic yarn.
Cover: Yellow Carbryn™ synthetic rubber, RMA Class A (high oil resistance) MSHA approved.

TEMPERATURE RANGE

-29°C to 99°C.

For asset management please refer to the accessories section on page 245.