





# ORTAC®

## AIR & MULTIPURPOSE



### Product specifications

#							Length
	inch	mm	mm	bar	psi	kg/m	m
20026560	3/16	5.0	11.8	20.7	300	0.10	152.4
20026527	1/4	6.0	13.5	20.7	300	0.13	152.4
20026529	5/16	8.0	17.5	20.7	300	0.21	152.4
20026531	3/8	10.0	17.5	20.7	300	0.22	152.4
20026534	1/2	12.0	21.3	20.7	300	0.30	152.4
20026570	5/8	16.0	26.9	20.7	300	0.52	152.4
20026540	3/4	19.0	29.0	20.7	300	0.51	152.4
20026575	1	25.0	38.1	20.7	300	0.88	137.2
20026579	1 1/4	32.0	45.2	17.2	250	1.04	122.0
20023267	1 1/2	38.0	52.8	17.2	250	1.43	91.4
20024996	2	50.0	63.5	13.8	200	1.80	30.5

### APPLICATIONS

Ortac® (oil resistant tube and cover) is our most popular premium-quality multipurpose hose. Used in the most abusive industrial applications, Ortac will handle air, oil, water, kerosene and some chemicals. Non-conductive, minimum electrical resistance greater than one (1) megohm per inch of hose length; at 1000 Volts DC. Available in 250, 300 and 400 PSI working pressures.

**Note:** Ortac® 400 Yellow is USMSHA approved.

### FEATURES

- Premium quality
- Non-conductive

### CONSTRUCTION

**Core tube:** Nitrile synthetic rubber, RMA Class A (high oil resistance).  
**Pressure reinforcement:** Spiral synthetic yarn, 2" is braided.  
**Cover:** Red or Yellow Carbryn™ synthetic rubber, RMA Class A (high oil resistance).

### TEMPERATURE RANGE

-29°C to 99°C.



**Please Note:** We reserve the right to make technical changes without notice.