








Product specifications

#							Vacuum HG		
	inch	mm		mm	bar		psi	mm	
20013527	1 1/4	31.8	41.4	3.1	45	76.0	737.0	29	0.51
20013528	1 1/2	38.1	48.0	2.8	40	81.0	737.0	29	0.60
20013529	2	50.8	62.7	2.8	40	140.0	737.0	29	1.00
20013531	2 1/2	63.5	77.5	2.4	35	152.0	737.0	29	1.29
20013532	3	76.2	93.7	2.1	30	191.0	737.0	29	1.73
20013535	4	101.6	122.2	2.1	30	279.0	737.0	29	3.21
20013539	5	127.0	146.8	2.1	30	381.0	737.0	29	3.87
20013545	6	152.4	179.8	1.7	25	508.0	737.0	29	5.10
20013549	8	203.2	234.2	1.4	20	762.0	737.0	29	8.69
20013554	10	254.0	284.7	1.4	20	1143.0	737.0	29	11.85

APPLICATIONS

The Artrac® hose is used for a variety of abrasive, material handling applications to transfer sand, gravel, cement, fly ash, glass, metals, plastic pellets, fertilizers, rock salts and slurries.

FEATURES

- Premium quality
- Lightweight

CONSTRUCTION

Core tube: Thermoplastic alloyed blend of polyurethane and PVC (static dissipating / static conductive).

Pressure reinforcement: Rigid high-density PVC helix.

Cover: Thermoplastic alloyed blend of nitrile, polyurethane, and PVC (non-conductive).

TEMPERATURE RANGE

-40°C to 70°C.