





BLACK GOLD® BULK MATERIAL 300D

OIL & GAS INDUSTRIAL HOSE



Product specifications

#									Length		Vacuum
	inch	mm		mm	bar	psi	bar		psi	kg/mtr	
3129-1000	3	76	3.98	20.7	300	82.7	1200	1.3	200	10	10
3129-1001	4	102	4.98	20.7	300	82.7	1200	1.5	200	10	10
3129-1002	5	127	6.14	20.7	300	82.7	1200	2.1	100	10	10
3129-1003	6	152	7.14	17.2	250	68.9	1000	2.5	100	10	10

APPLICATIONS

Transfer of abrasive materials such as barite and cement from a supply ship to an offshore drilling rig or platform; and for transfer applications on offshore or onshore drilling rigs or platforms. The natural rubber tube is specially compounded to conduct electricity and made with extra thickness to resist abrasion. The heavy duty reinforcement is designed to survive extreme oilfield application requirements.

FEATURES

- The specially compounded cover material is designed to withstand the harshest environment including abrasion and weathering.
- Design Factor 4:1.
- ABS and DNV Type approval.

CONSTRUCTION

Core tube: Type D3 (Natural Rubber). Specially compounded to conduct electricity.
Pressure reinforcement: Synthetic, high tensile textile.
Cover: Type D (SBR).
Design Factor: 4:1

TEMPERATURE RANGE

-40°C to 66°C.

Please Note: We reserve the right to make technical changes without notice.