







# BLACK GOLD® BULK MATERIAL 300SD OIL & GAS INDUSTRIAL HOSE

## Product specifications

#										Length		Vacuum	
	inch	mm		mm	bar	psi	bar			psi	mm	kg/mtr	ft
4691-0017	3	76	4.23	20.7	300	82.7	1200	813	1.6	200	29		
4691-0018	4	102	5.30	20.7	300	82.7	1200	1067	2.4	200	29		
4691-0019	5	127	6.33	20.7	300	82.7	1200	1295	2.7	200	29		
4691-0020	6	152	7.33	20.7	300	82.7	1200	1524	3.3	200	29		

## APPLICATIONS

Transfer of abrasive materials such as barite and cement from a supply ship to an offshore drilling rig or platform; and for transfer applications on offshore or onshore drilling rigs or platforms. The natural rubber tube is specially compounded to conduct electricity and made with extra thickness to resist abrasion. The heavy duty reinforcement is designed to survive extreme oilfield application requirements.

## FEATURES

- Suitable for suction and delivery applications.
- Design Factor 4:1.
- ABS and DNV Type approval.

## CONSTRUCTION

**Core tube:** Type D3 (Natural Rubber).  
**Pressure reinforcement:** Synthetic, high tensile textile with steel wire helix.  
**Cover:** Type D (SBR).  
**Design Factor:** 4:1

## TEMPERATURE RANGE

-40°C to 66°C.

**Please Note:** We reserve the right to make technical changes without notice.