






BLACK GOLD® FUEL 300D

OIL & GAS INDUSTRIAL HOSE



Product specifications

#								Vacuum		
	inch	mm		bar	psi				bar	psi
4110-0701	2	50.8	67.5	20.7	300	83	1200	14	0.8	10
4110-0704	2 1/2	63.5	80.2	20.7	300	83	1200	17	1.0	10
4110-0707	3	76.2	93.9	20.7	300	83	1200	21	1.1	10
4110-0710	4	101.6	119.3	20.7	300	83	1200	28	1.4	10
4110-0713	5	127	148.3	20.7	300	83	1200	35	2.0	10

APPLICATIONS

Transfer of refined fuels (commercial gasoline, diesel fuel) oils and other petroleum products. Ideal for offshore / onshore transfer applications involving discharge service for diesel oils and other similar petroleum products where an extremely lightweight, flexible hose with a high rated working pressure and a small minimum bend radius is required. Transfer of water, petroleum-based fluids, dilute acids, chemicals and abrasive slurries used in oil and gas well stimulation and fracking.

FEATURES

- Electrically conductive.
- Flexible with a high working pressure.
- ABS and DNV Type approval.

CONSTRUCTION

Core tube: Type C (Nitrile).
Pressure reinforcement: Synthetic, high tensile textile with static wire.
Cover: Type A (Chloroprene).
Design Factor: 4:1

TEMPERATURE RANGE

-40°C to +82°C.

Please Note: We reserve the right to make technical changes without notice.