









# BLACK GOLD® FUEL 300SD OIL & GAS INDUSTRIAL HOSE

## Product specifications

#										Vacuum
	inch	mm		mm	bar	psi	bar			
4688-0584	2	50.8	70.6	20.7	300	83	1200	12	0.5	30
4688-0585	3	76.2	98.0	20.7	300	83	1200	24	1.2	30
4688-0587	4	101.6	123.6	20.7	300	83	1200	30	1.4	30
4688-0588	6	152.4	179.5	13.7	200	83	1200	40	3.4	30

## APPLICATIONS

Transfer of refined fuels (commercial gasoline and diesel fuel) oils and other petroleum products. Ideal for offshore / onshore transfer applications involving suction and discharge service for diesel oils and other similar petroleum products where an extremely lightweight, hardwall, flexible hose with a high rated working pressure and a small minimum bend radius is required. Transfer of water, petroleum-based fluids, dilute acids, chemicals and abrasive slurries used in oil and gas well stimulation and fracking.

## FEATURES

- Electrically conductive.
- Flexible with a high working pressure.
- Suitable for suction and delivery applications.
- ABS and DNV Type approval.

## CONSTRUCTION

**Core tube:** Type C (Nitrile).  
**Pressure reinforcement:** Synthetic, high tensile textile with steel wire helix.  
**Cover:** Type A (Chloroprene).  
**Design Factor:** 4:1

## TEMPERATURE RANGE

-40°C to +82°C.

**Please Note:** We reserve the right to make technical changes without notice.