






CHEM MASTER™ PLUS XLPE (150-200) SD OIL & GAS INDUSTRIAL HOSE



Product specifications

#								Length	Vacuum	Colour
	inch	mm		bar	psi					
4695-0002	3/4	19.1	1.25	13.8	200	4.0	0.20	100	30	Black
4695-0737	3/4	19.1	1.25	13.8	200	4.0	0.20	200	30	Black
4695-0003	1	25.4	1.50	13.8	200	5.0	0.25	100	30	Black
4695-0670	1	25.4	1.50	13.8	200	5.0	0.25	200	30	Black
4695-0004	1 1/4	31.8	1.75	13.8	200	6.0	0.31	100	30	Black
4695-0738	1 1/4	31.8	1.75	13.8	200	6.0	0.31	200	30	Black
4695-0005	1 1/2	31.8	2.04	13.8	200	8.0	0.39	100	30	Black
4695-0729	1 1/2	31.8	2.04	13.8	200	8.0	0.31	200	30	Black
4695-0001	2	50.8	2.54	13.8	200	9.0	0.48	100	30	Black
4695-0698	2	50.8	2.54	13.8	200	9.0	0.48	200	30	Black
4695-0006	2 1/2	63.5	3.05	10.3	150	12.0	0.63	100	30	Black
4695-0720	2 1/2	63.5	3.05	10.3	150	12.0	0.63	200	30	Black
4695-0007	3	76.2	3.58	10.3	150	18.0	0.82	100	30	Black
4695-0699	3	76.2	3.58	10.3	150	18.0	0.82	200	30	Black
4695-0008	4	101.6	4.69	10.3	150	24.0	1.23	100	30	Black
4695-0055	4	101.6	4.69	10.3	150	24.0	1.23	200	30	Black
4695-0628	1	25.4	1.50	13.8	200	5.0	0.25	100	30	Green
4695-0211	1 1/2	38.1	2.04	13.8	200	8.0	0.39	100	30	Green
4695-0216	2	50.8	2.54	13.8	200	9.0	0.48	100	30	Green
4695-0700	2	50.8	2.54	13.8	200	9.0	0.48	200	30	Green
4695-0774	2 1/2	63.5	3.05	10.3	150	12.0	0.58	100	30	Green
4695-0229	3	76.2	3.58	10.3	150	18.0	0.82	100	30	Green
4695-0701	3	76.2	3.58	10.3	150	18.0	0.82	200	30	Green

APPLICATIONS

Tank truck, barge, ship, or storage tank transfer of a variety of chemical products. Chem Master™ Plus XLPE contains a wire helix for full suction capability, as well as for routing hoses through tight bends. Its Modified Cross-linked Polyethylene tube stock is 'best in class' for maintaining a tight seal with stainless steel fittings, and is designed for cleaning with 'open-end' 50 psi steam or in a bath containing 10% (NaOH) at +212°F (+100°C).

FEATURES

- Applications include 950 basic chemicals
- Light and flexible for ease of handling
- ABS and DNV Type Approval

CONSTRUCTION

Core tube: Type K (Gatron™ Modified Cross-linked Polyethylene). Tan. High chemical resistance.
Reinforcement: Synthetic, high tensile textile cord with steel wire helix.
Cover: Type P (EPDM). Black or green corrugated with orange stripe.
Design Factor: 4:1

TEMPERATURE RANGE

-40°C to +121°C.

Please Note: We reserve the right to make technical changes without notice.