





# FLEXSTEEL PETROL PETROLEUM TRANSFER



## Product specifications

#							Length
	inch	mm	mm	bar	psi	kg/m	m
20022226	5/8	16.0	25.4	2.5	36	0.51	145-190
20022229	3/4	19.0	20.2	2.5	36	0.67	145-190
20022230	1	25.0	38.1	2.5	36	0.91	100-160

## APPLICATIONS

Flexsteel Petrol Pump hose is a hose which offers excellent kink resistance in petrol dispensing applications. Meeting the performance criteria of AS2683-1989 Type 4, Grade 2, Kind 1 and 2. Its wire-braid reinforcing, coupled with Contitech specially developed compounds (intrinsically conducting), make this the safest and most durable hose available for this application

## FEATURES

- Excellent Kink resistance
- Hardwall for long service life
- Smooth cover prevents marking
- Meets AS2683 Standard

## CONSTRUCTION

<b>Core tube:</b>	Black Chemigum® (Nitrile).
<b>Pressure reinforcement:</b>	Single braided high tensile wire.
<b>Cover:</b>	Black Chemivic® (Nitrile blend).
<b>Branding:</b>	Contitech 5/8" Flexsteel Petrol Pump – AS2683-1989 Type 4, Grade 2, Kind 1 and 2, 250 Kpa W.P.

## TEMPERATURE RANGE

-29°C to 82°C.



**Please Note:** We reserve the right to make technical changes without notice.