

# PLICORD® EXTREMEFLEX™ PETROLEUM TRANSFER



PLICORD® EXTREMEFLEX™ - PETROLEUM TRANSFER

## Product specifications

#	Ø		Ø	P		R		Vacuum HG		Kg	Length
	inch	mm		bar	psi	mm	inch	mm	inch		
20459042	3/4	19.0	30.5	17.2	250	19.0	0.75	737.0	29	0.65	30.48
20459043	1	25.4	36.8	17.2	250	25.0	1	737.0	29	0.81	30.48
20472432	1 1/4	32.0	42.5	17.2	250	32.0	1.25	737.0	29	0.88	30.48
20459044	1 1/2	38.0	48.5	17.2	250	37.1	1.5	737.0	29	1.08	30.48
20474865	1 1/2	38.0	48.5	17.2	250	37.1	1.5	737.0	29	1.08	60.96
20635998	1 3/4	44.0	55.8	17.2	250	44.0	1.73	737.0	29	1.28	121.92
20459045	2	50.0	61.8	17.2	250	50.8	2	737.0	29	1.46	30.48
20474866	2	50.0	61.8	17.2	250	50.8	2	737.0	29	1.46	60.96
20459046	2 1/2	63.0	76.1	13.7	200	63.5	2.5	737.0	29	2.10	30.48
20459047	3	75.0	88.8	13.7	200	76.2	3	737.0	29	2.51	30.48
20607374	3 1/2	88.0	103.6	10.3	150	88.0	3.43	737.0	29	3.21	30.48
20459048	4	100.0	115.7	10.3	150	101.6	4	737.0	29	3.61	30.48
20546328	6	150.0	168.1	10.3	150	150.0	6	737.0	29	6.61	30.48

## APPLICATIONS

An extremely flexible and lightweight drop hose for use in tank truck and in-plant operation to transfer diesel, ethanol, gasoline, oil and petroleum base products up to 60% aromatic content. Corrugated construction for lower drag coefficient and superior abrasion resistance.

## FEATURES

- Extremely flexible
- Lightweight
- Weather and ozone resistant

## CONSTRUCTION

**Core tube:** Black Nitrile synthetic rubber (Class A oil resistance).  
**Pressure reinforcement:** Spiral plied synthetic fabric with wire helix.  
**Cover:** Black Chemivic™ synthetic (corrugated).

## TEMPERATURE RANGE

-40°C to 93°C.



**Continental** ContiTech

**Please Note:** We reserve the right to make technical changes without notice.