








# PLICORD® SUPER BLACK FLEXWING® PETROLEUM TRANSFER

#									Vacuum HG		
	inch	mm	mm	bar	psi	mm	inch	mm	inch	kg/m	
20155914	1 1/4	31.8	47.1	20.7	300	100.0	4	737.0	29	1.48	
20017550	1 1/2	38.1	52.8	20.7	300	100.0	4	737.0	29	1.71	
20017552	2	50.8	65.8	20.7	300	125.0	5	737.0	29	2.14	
20017558	2 1/2	63.5	79.0	20.7	300	150.0	6	737.0	29	2.74	
20017560	3	76.2	92.7	20.7	300	175.0	7	737.0	29	3.56	
20017564	4	101.6	122.7	20.7	300	254.0	10	737.0	29	5.60	
20017568	5	127.0	149.0	20.7	300	500.0	20	737.0	29	7.60	
20338990	6	152.4	183.3	20.7	300	600.0	24	737.0	29	12.60	

## APPLICATIONS

A premium high-pressure petroleum transfer hose for handling ethanol blends, gasoline, oils and other petroleum products at higher working pressures.

## FEATURES

- Premium quality
- Weather and ozone resistant
- Early warning system for external wear

## CONSTRUCTION

**Core tube:** Special fuel-resistant black nitrile synthetic rubber RMA Class A (High oil resistance)

**Pressure reinforcement:** Spiral-plied synthetic fabric with wire helix

**Cover:** Black Chemivic™ smooth cover with wrapped finish. Also available with ARC treatment for improved abrasion resistance. Both hoses standard with built in blue wear ply to illustrate wear condition and potential trigger point for product replacement.

## TEMPERATURE RANGE

-37°C to 93°C.



**Please Note:** We reserve the right to make technical changes without notice.